


Rectangle Tube



FINISH: Mill

STOCK CODE	DESCRIPTION W x H x T	ALLOY TEMPER	LENGTH METRE	WEIGHT KG/M	ANOD PER	STATE		
						V	N	Q
RET38173	38.1 x 17.45 x 3.18	6060 T5	6.5	0.85	111	●	●	●
RET382516	38.0 x 25.0 x 1.6	6060 T5	6.5	0.47	121	●		●
RET382525	38.1 x 25.4 x 2.54	6060 T5	6.5	0.8	127	●	●	
RET40203	40.0 x 20.0 x 3.0	6060 T5	6.5	0.88	127	●	●	●
RET402525	40.0 x 25.0 x 2.5	6060 T5	6.5	0.81	246	●	●	●
RET502516	50.0 x 25.0 x 1.6	6060 T5	6.5	0.623	150	●		●
RET502525	50.0 x 25.0 x 2.5	6060 T5	6.5	0.95	150	●	●	●
RET50253	50.0 x 25.0 x 3.0	6060 T5	6.5	1.12	150	●	●	●
RET50383	50.8 x 38.1 x 3.18	6060 T5	6.5	1.44	177	●	●	
RET504025	50.0 x 40.0 x 2.5	6060 T5	6.5	1.148	180			●
RET60403	60.0 x 40.0 x 3.0	6060 T5	6.5	1.52	200	●	●	●
RET762516	76.0 x 25.0 x 1.6	6060 T5	6.5	0.81	220	●	●	●
RET762524	76.2 x 25.4 x 2.4	6060 T5	6.5	1.255	220	●	●	●
RET76383	76.2 x 38.1 x 3.18	6060 T5	6.5	1.95	228	●	●	
RET76503	76.2 x 50.8 x 3.18	6060 T5	6.5	2.08	254	●	●	
RET75506	75.0 x 50.0 x 6.0	6082 T6	6	3.68	250	●		
RET80253	80.0 x 25.0 x 3.0	6060 T5	6.5	1.604	225		●	●
RET80403	80.0 x 40.0 x 3.0	6060 T5	6.5	1.85	240	●	●	●
RET80503	80.0 x 50.0 x 3.0	6060 T5	6.5	2.01	260	●	●	●
RET822822	82.28 x 28.28 x 2.2	6060 T5	6.5	1.32	222	●	●	
RET1002525	100.0 x 25.0 x 2.5	6060 T5	6.5	1.62	250	●	●	●
RET1005016	100.0 x 50.0 x 1.6	6060 T5	6.5	1.27	300	●	●	●
RET100503	100.0 x 50.0 x 3.0	6060 T5	6.5	2.33	300	●	●	●
RET125403	125.0 x 40.0 x 3.0	6060 T5	6.5	2.585	300			●
RET150503	150.0 x 50.0 x 3.0	6060 T5	6.5	3.15	400	●	●	●
RET200503	200.0 x 50.0 x 3.0	6060 T5	6.5	3.96	500	●	●	●
RET250503	250.0 x 50.0 x 3.0	6060 T5	6.5	4.736	600		●	●

Rectangle Tube Radius

FINISH: Mill


STOCK CODE	DESCRIPTION W x H x T	ALLOY TEMPER	RADIUS		LENGTH METRE	WEIGHT KG/M	ANOD PER	STATE		
			OR	IR				V	N	Q
RETR382516	38.0 x 25.0 x 1.6	6060 T5	3	1.5	6.5	0.47	121			●
RET382519	38.0 x 25.0 x 1.9	6060 T5	3	1.5	6.5	0.589	121		●	
RETR38252	38.0 x 25.0 x 2.0	6060 T5	3	1.5	6.5	0.637	121			●
RETR501016	50.0 x 10.0 x 1.6	6060 T5	0.4	0.4	6.5	0.41	120	●	●	
RETR502516	50.0 x 25.0 x 1.6	6060 T5	3	1.5	6.5	0.605	150			●
RETR50253	50.0 x 25.0 x 3.0	6060 T5	3		6.5	1.101	150			●
RETR651614	65.0 x 16.0 x 1.4	6060 T5	3	1.6	6.5	0.576	162	●	●	●
RETR75503	75.0 x 50.0 x 3.0	6060 T5		6	6.5	1.872	250			●
RETR75504	75.0 x 50.0 x 4.0	6005A T5	1	5	7.5	2.479	250			●
RETR76506	76.2 x 50.8 x 6.35	6106 T6	1	1	6.5	3.919	252			●
RETR80403	80.0 x 40.0 x 3.0	6060 T5	4.7	6	6.5	1.815	240			●
RETR80503	80.0 x 50.0 x 3.0	6060 T5	4.7	6	6.5	1.97	240			●
RETR1001614	100.0 x 16.0 x 1.4	6060 T5	3		6.5	0.78	227			●
RETR100503	100.0 x 50.0 x 3.0	6060 T5	6	3	6.5	2.27	300	●	●	●
RETR100506	100.0 x 50.0 x 6.0	6061 T6	6	2	6.5	4.35	286	●	●	●
RETR100253	100.0 x 25.0 x 3.0	6060 T5	4	2.5	6.5	1.866	240			●
RETR150503	150.0 x 50.0 x 3.0	6060 T5	4	3	6.5	3.092	340			●

Other sizes and variations may be available – contact your nearest branch for assistance.



Rectangle Tube

ALLOY: 6060 TEMPER: T5 FINISH: White & Primrose



STOCK CODE	DESCRIPTION W x H x T	LENGTH METRE	WEIGHT KG/M	ANOD PER	STATE		
					V	N	Q
RET200503W	200.0 x 50.0 x 3.0	6.5	3.96	500			●
RET200503P	200.0 x 50.0 x 3.0	6.5	3.96	500			●

Other sizes and variations may be available – contact your nearest branch for assistance.

