


Round Tube




FINISH: Mill

STOCK CODE	DESCRIPTION D x T	ALLOY TEMPER	LENGTH METRE	WEIGHT KG/M	ANOD PER	STATE		
						V	N	Q
ROT69	6.35 x 0.91	6060 T5	6	0.04	100	●	●	●
ROT1012	10.0 x 1.2	6060 T5	6.5	0.09	100	●		●
ROT1012-5	10.0 x 1.2	6060 T5	5	0.09	100	●		
ROT1016	10.0 x 1.6	6060 T5	6.5	0.11	100	●	●	●
ROT1216	12.0 x 1.6	6060 T5	6.5	0.14	100	●	●	●
ROT1415	14.0 x 1.5	6060 T5	4	0.16	100	●	●	●
ROT1512-6	15.88 x 1.22	6060 T5	6	0.152	100			●
ROT1616	16.0 x 1.6	6060 T5	6.5	0.2	100	●	●	●
ROT1912	19.0 x 1.2	6060 T5	6.1	0.181	100			●
ROT2016	20.0 x 1.6	6060 T5	6.5	0.25	100	●	●	●
ROT202	20.0 x 2.0	6060 T5	6.5	0.305	100			●
ROT203	20.0 x 3.0	6060 T5	6.5	0.433	100	●	●	●
ROT2516	25.0 x 1.6	6060 T5	6.5	0.33	100	●	●	●
ROT253	25.0 x 3.0	6060 T5	6.5	0.56	100	●	●	●
ROT3216	32.0 x 1.6	6060 T5	6.5	0.42	100	●	●	●
ROT323	32.0 x 3.0	6060 T5	6.5	0.74	100	●	●	●
ROT383	38.1 x 3.25	6060 T5	6.5	0.9	119	●	●	●
ROT4016	40.0 x 1.6	6060 T5	6.5	0.52	125	●	●	●
ROT403	40.0 x 3.0	6060 T5	6.5	0.94	125	●	●	●
ROT4416	44.0 x 1.6	6060 T5	6.5	0.53	138	●	●	●
ROT443	44.4 x 3.0	6060 T5	6.5	1.141	246	●	●	●
ROT4816	48.0 x 1.6	6060 T5	6.5	0.63	151	●	●	●
ROT4844	48.44 x 4.47	6061 T6	6.1	1.67	152	●	●	●
ROT5016	50.0 x 1.6	6060 T5	6.5	0.66	157	●	●	●
ROT502	50.0 x 2.0	6060 T5	6.5	0.81	157			●
ROT503	50.0 x 3.0	6060 T5	6.5	1.2	157	●	●	●
ROT504	50.0 x 4.0	6060 T5	6.5	1.56	157			●
ROT505	50.0 x 5.0	6060 T5	6.5	1.909	157			●
ROT506	50.0 x 6.0	6060 T5	6.5	2.39	157	●	●	●
ROT602	60.0 x 2.0	6060 T5	6.5	0.99	188	●	●	●
ROT603	60.0 x 3.0	6060 T5	6.5	1.45	188	●	●	●
ROT605	60.0 x 5.0	6060 T5	6.5	2.34	189	●	●	●
ROT636	63.5 x 6.35	6060 T5	6.5	3.09	199	●	●	●
ROT757	75.0 x 7.0	6061 T6	6.5	4.032	238			●
ROT7632	76.2 x 3.25	6060 T5	6.5	2.01	215	●		●
ROT7647	76.2 x 4.75	6060 T5	6.5	2.89	239	●	●	●
ROT766	76.2 x 6.35	6061 T6 / 6005A T5	6.5	3.76	239		●	●
ROT802	80.0 x 2.0	6060 T5	6.5	1.32	251	●	●	●
ROT803	80.0 x 3.0	6060 T5	6.5	1.96	251	●	●	●
ROT889635	88.9 x 6.35	6061 T6	6.5	4.463	282	●		●
ROT1002	100.0 x 2.0	6060 T5	6.5	1.67	314	●	●	●
ROT1003	100.0 x 3.0	6060 T5	6.5	2.48	314	●	●	●
ROT10164	101.6 x 6.4	6061 T6	6.5	5.149	322	●	●	●
ROT11463	114.3 x 6.35	6061 T6	6.5	5.836	362			●
ROT1178	117.0 x 8.0	6005A T5	6.5	7.424	371			●
ROT12563	125.0 x 6.35	6005A T5	6.5	6.414	393			●
ROT1503	150.0 x 3.0	6060 T5	6.5	3.76	479	●	●	●
ROT2033	203.2 x 3.0	6060 T5	6.5	5.094	638			●

Other sizes and variations may be available – contact your nearest branch for assistance.



Telescopic Tube



FINISH: Mill

STOCK CODE	DESCRIPTION D x T	ALLOY TEMPER	LENGTH METRE	WEIGHT KG/M	ANOD PER	STATE		
						V	N	Q
ROT1214	12.7 x 1.42	6060 T6	5.5	0.14	100	●	●	●
ROT1514	15.58 x 1.42	6060 T6	5.5	0.17	100	●	●	●
ROT1914	19.05 x 1.42	6060 T6	5.5	0.21	100	●	●	●
ROT2214	22.22 x 1.42	6060 T6	5.5	0.25	100	●	●	●
ROT2514	25.4 x 1.42	6060 T6	5.5	0.29	100	●	●	●
ROT2814	28.58 x 1.42	6060 T6	5.5	0.33	100	●	●	●

Round Tube

FINISH: Clear Anodised & Bright Dipped

STOCK CODE	DESCRIPTION D x T	ALLOY TEMPER	LENGTH METRE	WEIGHT KG/M	ANOD PER	STATE		
						V	N	Q
ROTC2016 (Clear)	20.0 x 1.6	6060 T5	6.5	0.25	100	●		
ROTC2516 (Clear)	25.0 x 1.6	6060 T5	6.5	0.33	100	●	●	
ROTBDD2516 (B.Dipped)	25.0 x 1.6	6060 T5	6.5	0.33	100	●	●	
ROTBDD253 (B.Dipped)	25.0 x 3.0	6060 T5	6.5	0.56	100	●		

Other sizes and variations may be available – contact your nearest branch for assistance.

